



August 14 1894
Commenced Survey of Section
5 Town 7 North,
Range 6 West.

I went to John
E. Mitchell in section
5 Town 7 N Range 6 W
to begin survey pur-
suant to notice of
William Leach for Survey
of Secs. 5 & 9 said town
& Range but on ac-
count of rain and unfa-
vorable weather post-
poned said survey until August 21st 1894 H.M. Parker
Dep. Surveyor

found said survey until August 21st 1894 H.M. Parker
Dep. Surveyor

Tuesday Aug 21st I commenced Survey of Section 5 Township
7 North of Range 6 West. Mr. Parker Dep. Surveyor, having
advised Survey from Aug 14th to this date. William Leach
being Survey. Says that 10 days notice had been served on all
resident owners, and by 3 weeks publication in 'Linton Call' weekly
newspaper published at Linton Green County, Indiana. The affidavit
of William Leach and copy of notice served filed in their office.
I commenced at the North East Corner of Section 5.
Thence met 80.14 to the North West Corner (this Chaining
to more accurate than previous one) & Links North of Corner
where 40.07 Chain and located the East N¹/₄ Cor of
Section 5. Then commenced at SE Corner of Section
5. at a corner I located four miles past (See page 195)
Thence met 80.04 to a point 2.30 Chain South and
1.84 Chains west of a stone set for Cor Section 5-6-7-8
having commenced a Survey of this Section in December
1892 (See record 6 pg 133) and found that this point
was a proportionate distance and with the records of
the Government Survey. by taking the corner East by
Kelshaw in 1838 as the original quarter corner
for Section 7, T. 6. This point would

Corners Established.	Monument.	Bearing Trees.	Diameter in Inches.	Course.	Links Distant.
----------------------	-----------	----------------	------------------------	---------	-------------------

in proportion to the Chaining I made in 1892. and
in chaining from a corner East by Parker at the
South East Corner of Section 7. North to the NW corner of Section
5. a distance as shown by the Chain of 162.07 Chain
a loss of 4.8 Links from the distance given in
the Government field notes. I located the corner
of Section 5-6-7-8. being S 30 1/2 W 2.42 1/2 Chain
from a stone set for this corner. as this stone has
been rigidified at the corner for several years and would
make the fraction that belong to the North line of quarter
Section in Section 5, T. 6. held in Section 7, T. 8.
as the government in their survey made no B.T. for the
Cor of 5-6-7-8. the only way to find where they
placed the first for this corner is in the Chaining.
The Chaining E.T.W. is plus 5 N. 7, 8. Williams, as the
Subdivision of Section 5. hinges on this corner. after
locating it. I proceed to subdivide the Section. by
running cross quarter lines from opposite quarter
corner & making Cent' Cor at the intersection of quarter
lines. and quarter quarter corner at equal distance
from quarters Cor on E & W N. 7, 8 from Cent' Cor. See
plat for diagram and made the following corner

N ¹ / ₄ NW	Stone	White Oak	20	S 32° W	60
S ¹ / ₄ E	"	Small Slender burned elm trees		North	50
S ¹ / ₄ SE	"	"		S 0.30' E	66 1/2
S ¹ / ₄ SW	"	"		N 0.30' W	25
N ¹ / ₄ SW	"	"		N 0.30' W	28
Cent' SW	"	"		N 0.30' W	27 1/2
Cent' W	"	"		N 0.30' W	28
N ¹ / ₄ NE	"	"		East	35
Cent' NE	"	"		S 0.30' E	25
S ¹ / ₄ NE	"	"		West	25
NE added	"	"		S 45° W	45

at this corner one of my B.T. has blown down.

Wm Page } Ch B
Harry Corn } 2 B } done
John Corbsey }
E. Fide Cor
S. G. L.